Multipurpose Lithium Grease

High Performance

Description:

SN-MP2 100 is a mineral oil based Lithium grease fortified with, **anti-wear**, **anti-oxidation** and **anti-corrosion** additives. This high performance grease is suitable for wide range of industrial and automotive applications.

Performance & Features:

- Good high temperature performance up to **130°C**
- Good oxidation resistance
- Excellent wear and corrosion protection
- Long storage life
- Good mechanical stability
- Equivalent to SHELL GADUS S2 V100 2 & SKF LGMT 2

Typical Applications:

- Electric motor bearing
- Automotive wheel bearing
- Agricultural equipment
- Water pump bearing
- Conveyors
- Industrial fans

Properties:

Specifications	Methods	Conditions	Unit	SN-MP2 100
Base oil type				Mineral oil
Base oil viscosity @ 40 °C	ASTM D 445		cSt (mm^2/s)	100
Thickener type				Lithium Soap
Dropping point	ASTM D566		°C	≥190
NLGI Consistency			NLGI- class	**2**
Worked penetration	ASTM D217	60 Dh	mm/10	265 – 295
Operating Temperature Range				-20 °C to + 130 °C
Colour				Yellow







+971 55 784 0677
www.sindaoil.ae info@sindaoil.ae PO Box: 376800
Rashid Building, 23B St, Oil Market, Naif, Deira, Dubai, United Arab Emirates