SiNDA
SiNDA Motor Oil Company

شركة سيندا لتجارة الزيوت ش.ذ.م.م
SiNDA OIL TRADING L.L.C

Multipurpose Calcium Sulfonate Complex Grease

Extreme Pressure (**EP**), High Temperature, Water Resistant

Description:

SN-CSX 222 is based on mineral oil and latest Calcium Sulfonate Complex thickener technology.
SN-CSX 222 is recommended for most types of industrial applications including heavy-duty applications where high unit pressures or shock loads, wet environments and high temperatures are present.

Performance & Features:

- Outstanding high temperature performance up to **200°C**
- Excellent oxidation resistance
- Excellent wear and corrosion protection
- Excellent **Extreme Pressure** performance
- Long life
- Excellent mechanical stability


Typical Applications:

- Heavy duty bearing and general industrial lubrication
- Loaders, Excavators, Cranes
- Stone crushers, Excavators
- Conveyors
- Car &Truck wheel bearing
- Pellet mills
- Pulp and paper making machines

Properties:

Specifications	Methods	Unit	SN-CSX 221	SN-CSX 222
Base oil type			Mineral oil	Mineral oil
Base oil viscosity @ 40 °C	ASTM D 445	cSt (mm²/s)	220	220
Thickener type			Calcium Sulfonate Complex	Calcium Sulfonate Complex
Dropping point	ASTM D566	°C	>300	>300
NLGI Consistency		NLGI- class	**1**	**2**
Worked penetration	ASTM D217	mm/10	310 – 340	265 – 295
Four Ball Weld Load	ASTM D 2596	Kgf	>=250	>=400
Water Washout	ASTM D 1264	% Loss	-	≤ 1.5 %
Operating Temperature Range			-20 °C to + 200 °C	-20 °C to + 200 °C
Colour			Yellow-Light Brown	Yellow-Light Brown



+971 55 784 0677
www.sindaoil.ae info@sindaoil.ae PO Box: 376800
Rashid Building, 23B St, Oil Market, Naif, Deira, Dubai, United Arab Emirates